

HaloX® concrete installation housing (precast concrete)



System magnet

- for accurate positioning during automated or manual production
- with an anti-twist device for one-gang boxes
- adhesive force 500 N (50 kg)
- Can be used for the following articles:
 - HaloX® installation housing / item no. 1282-74/-75/-76 and 1283-74/-76
 - B² one-gang junction boxes / item no. 1262-06, 1263-06, 1264-06
 - 115 large slab ceiling box / item no. 1227-16
 - End and transition bushes / item no. 1261-82/-83/-84
 - Wall and ceiling transitions 30° / item no. 1261-92/-93/-94

Article no:	1299-69
EAN:	4013456552630
Type of accessory/spare part	Other
Accessory	Yes
Spare part	No
Suitable for built-in installation box	Yes
Suitable for central conduit box	Yes
Dispatch	10

System HaloX® is designed as a single piece for fitting in precast concrete. The housings can easily be aligned on the formwork table by means of markings on the housing. The housing with pre-fitted mineral fibreboard allows easy glueing and the housings can be turned by 360° on the formwork table even after glueing. Housings with pre-fitted front parts to hold the system magnet (Art. No. 1299-69/1299-70) are available for magnet attachment. Laying tolerances which may occur during the fitting of panel elements are compensated for via the housing sizes in connection with a variable cut-out area. Because of the compact dimensions of the housings, the reinforcement can easily be placed around the housing. For luminaires or loudspeakers with installation depths equal to or greater than 110 mm, the installation compartment of the HaloX® housings can be increased on the on-site concrete building site by means of extension rings. The fitting of the conduits on-site takes place without the need for tools for M20/M25 conduits without any internal shortening of the conduits.

- For precast concrete slab ceilings and wall elements.
- 3 housing sizes with and without tunnel
- Single-part housings with integrated mineral fibreboard for easy adhesive fixing
- One-part housings with plastic panel for magnet attachment
- Toolless entry technology for M20/M25 conduits
- Compensation for laying tolerances on the concrete building site
- Optimal heat management thanks to maximum surface contact with the concrete

