

## New Record

**CH75R-S5-BW, serieschakeling, brandwerend**

- 60 minutes fire-resistant
- Applicable in hollow ceiling constructions.
- Suitable for rachel ceilings and metal stud ceilings.
- Connectors from Wago-Winsta RD
- Equipped with 1x power supply (male black), 1x series switch (female brown), 1x light point feed-through (female white), 1x light point on central box cover.

|                                           |                     |
|-------------------------------------------|---------------------|
| <b>Article no:</b>                        | <b>AT1016</b>       |
| EAN:                                      | 8712259332741       |
| Amount Packaging                          | 1 st.               |
| Ø circular saw                            | 76 mm               |
| Outer size                                | 79 mm               |
| Switched                                  | Series switch       |
| Number of Outlets                         | 5                   |
| Mounting method                           | Hollow ceiling      |
| Degree of protection (IP)                 | IP20                |
| Material                                  | Plastic             |
| Width                                     |                     |
| Length                                    |                     |
| Diameter                                  | 76 mm               |
| Halogen free                              | Yes                 |
| Colour                                    | Red                 |
| Model                                     | Single              |
| Surface protection                        | Untreated           |
| Circuit integrity                         | E60                 |
| Cover model                               | Mounting cover      |
| Inner depth                               | 77 mm               |
| Degree of protection (NEMA)               | -                   |
| Equipped with                             | Other               |
| Shape                                     | Round               |
| Pipe locking                              | No                  |
| Construction type                         | Central conduit box |
| Number of inlets                          | 12                  |
| Air tight                                 | No                  |
| For tube diameter                         | 16/19 mm            |
| Max. conductor cross section              | 2.5 mm <sup>2</sup> |
| Inlet from the rear                       | No                  |
| Transparent cover                         | No                  |
| Cover attachment                          | Screwed             |
| Sealable                                  | No                  |
| With screening                            | No                  |
| Provided with revolving ring              | No                  |
| Connectable                               | No                  |
| For number of electric fittings           |                     |
| Mounting switching equipment              | -                   |
| With screws                               | No                  |
| Housing feed-through by break-out opening | No                  |

|                                       |                    |
|---------------------------------------|--------------------|
| Housing feed-through by seal membrane | No                 |
| Housing feed-through by nozzle        | No                 |
| Housing feed-through by step membrane | No                 |
| Pipe locking optional                 | No                 |
| Number of included spouts             |                    |
| Number of poles of the clamp          |                    |
| Clamp position fixed                  | No                 |
| Luminaire hook mounting               | Yes                |
| Nozzle                                | Tunnel branch pipe |
| With nail lugs                        | No                 |
| Special application                   | Fire protection    |

Installeren RD is een stekbaar installatiesysteem gebaseerd op voorbedrade centraaldozen of kabeldozen in combinatie met prefab gemonteerd schakelmateriaal en een stekerbare groepenkast. Deze onderdelen worden met soepele kabels met ronde connectoren aangesloten. De installatietijd wordt daardoor sterk bekort, en faalkosten worden tot een minimum beperkt. 100% Installeren is een samenwerkingsverband van Gira, Jung, PEHA, WAGO en Attema.