

Central junction boxes concrete ceiling



CA70R Junction box 16/19 mm with tape Ø 16/19 mm

- Equipped with 9 combi-heads 16/19 mm.
- Applicable in solid floors and hollow core slab floors.
- Clip-resistant in borehole ø 80 mm.
- Matching covers: (art. no. AT5010 and art. no. AT5011).

| | |
|---|---------------------|
| Article no: | AT1019 |
| EAN: | 8712259314419 |
| Halogen free | Yes |
| Amount Packaging | 100 st. |
| Conduit diameter | 16 / 19 mm |
| Ø circular saw | 80 mm |
| Outer size | 115 mm |
| Mounting method | Concrete building |
| Degree of protection (IP) | IP20 |
| Material | Plastic |
| Width | |
| Length | |
| Diameter | 78 mm |
| Colour | Grey |
| Model | Single |
| Surface protection | Untreated |
| Circuit integrity | None |
| Cover model | None |
| Inner depth | 70 mm |
| Degree of protection (NEMA) | - |
| Equipped with | None |
| Shape | Round |
| Pipe locking | Yes |
| Construction type | Central conduit box |
| Number of inlets | 9 |
| Air tight | No |
| For tube diameter | 16/19 mm |
| Max. conductor cross section | 6 mm ² |
| Inlet from the rear | Yes |
| Transparent cover | No |
| Cover attachment | Screwed |
| Sealable | No |
| With screening | No |
| Provided with revolving ring | No |
| Connectable | No |
| For number of electric fittings | |
| Mounting switching equipment | - |
| With screws | No |
| Housing feed-through by break-out opening | No |
| Housing feed-through by seal membrane | No |
| Housing feed-through by nozzle | No |

| | |
|---------------------------------------|--------------------|
| Housing feed-through by step membrane | No |
| Pipe locking optional | No |
| Number of included spouts | |
| Number of poles of the clamp | |
| Clamp position fixed | No |
| Luminaire hook mounting | No |
| Nozzle | Tunnel branch pipe |
| With nail lugs | No |
| Special application | - |
| Dispatch | 100 |

The concrete ceiling junction boxes are specially developed for the installation of conventional systems in concrete ceilings. These junction boxes are equipped with combi-inlets combined for 16 mm and 19 mm conduits. The ceiling junction boxes Concrete are used in solid floors and concrete hollow-core floors, or precast slab floors.