


## Magvast concrete system junction boxes



### CD80R Junction box round with tape Ø 16/19 mm

- Can be used in wide boarded floors.
- Distance from the underside of the conduit entries to the open side of the box: 60 mm.
- The penetration of concrete water into conduit entries is prevented by adhesive tape.
- Protective cover (Art. No. AT4818) and adhesive protective cover (Art. No. AT4850) available separately.
- Suitable covers for mounting: Art. no. AT5010 and AT5011.

|   |                     |
|---|---------------------|
| <b>Article no:</b>                        | <b>AT1031</b>       |
| EAN:                                      | 8712259000114       |
| Halogen free                              | Yes                 |
| Amount Packaging                          | 54 st.              |
| Conduit diameter                          | 16 / 19 mm          |
| Ø circular saw                            | 80 mm               |
| Outer size                                | 85 mm               |
| Mounting method                           | Concrete building   |
| Degree of protection (IP)                 | IP20                |
| Material                                  | Plastic             |
| Width                                     |                     |
| Length                                    |                     |
| Diameter                                  | 77 mm               |
| Colour                                    | Grey                |
| Model                                     | Single              |
| Surface protection                        | Untreated           |
| Circuit integrity                         | None                |
| Cover model                               | None                |
| Inner depth                               | 80 mm               |
| Degree of protection (NEMA)               | -                   |
| Equipped with                             | -                   |
| Shape                                     | Round               |
| Pipe locking                              | No                  |
| Construction type                         | Central conduit box |
| Number of inlets                          | 8                   |
| Air tight                                 | No                  |
| For tube diameter                         | 16/19 mm            |
| Max. conductor cross section              | 6 mm <sup>2</sup>   |
| Inlet from the rear                       | No                  |
| Transparent cover                         | No                  |
| Cover attachment                          | Screwed             |
| Sealable                                  | No                  |
| With screening                            | No                  |
| Provided with revolving ring              | No                  |
| Connectable                               | No                  |
| For number of electric fittings           |                     |
| Mounting switching equipment              | -                   |
| With screws                               | No                  |
| Housing feed-through by break-out opening | No                  |
| Housing feed-through by seal membrane     | No                  |

|                                       |                    |
|---------------------------------------|--------------------|
| Housing feed-through by nozzle        | No                 |
| Housing feed-through by step membrane | No                 |
| Pipe locking optional                 | No                 |
| Number of included spouts             |                    |
| Number of poles of the clamp          |                    |
| Clamp position fixed                  | No                 |
| Luminaire hook mounting               | No                 |
| Nozzle                                | Tunnel branch pipe |
| With nail lugs                        | No                 |
| Special application                   | -                  |
| Dispatch                              | 54                 |

Attema's Magvast® concrete construction system is used mainly in concrete factories, but also on building sites. Magvast® works with magnets that are clamped into the boxes to prevent concrete water from entering the boxes.

After measuring, the magnets are placed on which the box is then placed. After the formwork is removed, the magnet remains behind on the steel table or formwork, after which it can be removed and reused. Magvast® is then ready for the next cycle. It is a flexible system that does not damage the formwork.

Attema has magnets for various types of boxes in its range. Magnets have a high clamping force (>100 kg).

Suitable for steel formwork.

Attached without drilling, so no damage to the formwork.