


Magvast concrete system junction boxes



MD-CD80R centre ceiling box

- Can be used in wide boarded floors.
- Distance from the underside of the conduit entries to the open side of the box: 60 mm.
- The penetration of concrete water into conduit entries is prevented by adhesive tape.
- Protective cover (Art. No. AT4818) and adhesive protective cover (Art. No. AT4850) available separately.
- Suitable covers for mounting: Art. no. AT5010 and AT5011.

Article no:	AT1032
EAN:	8712259545127
Halogen free	Yes
Amount Packaging	54 st.
Conduit diameter	16 / 19 mm
Ø circular saw	80 mm
Outer size	85 mm
Mounting method	Concrete building
Degree of protection (IP)	IP20
Material	Plastic
Diameter	77 mm
Colour	Grey
Model	Single
Surface protection	Untreated
Circuit integrity	None
Cover model	None
Inner depth	80 mm
Equipped with	None
Shape	Round
Pipe locking	No
Construction type	Central conduit box
Number of inlets	8
Air tight	No
For tube diameter	16/19 mm
Max. conductor cross section	6 mm ²
Inlet from the rear	No
Transparent cover	No
Cover attachment	Snapped on
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	No
Suitable for wall/board thickness	50 - 60 mm
For number of electric fittings	
With screws	No
Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	Yes
Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No

Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	None
Dispatch	54

Attema's Magvast® concrete construction system is used mainly in concrete factories, but also on building sites. Magvast® works with magnets that are clamped into the boxes to prevent concrete water from entering the boxes.

After measuring, the magnets are placed on which the box is then placed. After the formwork is removed, the magnet remains behind on the steel table or formwork, after which it can be removed and reused. Magvast® is then ready for the next cycle. It is a flexible system that does not damage the formwork.

Attema has magnets for various types of boxes in its range. Magnets have a high clamping force (>100 kg).

Suitable for steel formwork.

Attached without drilling, so no damage to the formwork.