


Central junction boxes concrete ceiling



CD100R Junction box, round, in plastic bag Ø 16/19 mm

- Can be used in wide boarded floors.
- Distance from the bottom of the conduit entry to the open side of the box: 80 mm.
- Plastic bag against ingress of concrete water.
- Protective cover (Art. No. AT4818) and adhesive protective cover (Art. No. AT4850) available separately.
- Suitable covers for mounting: Art. no. AT5010 and AT5011.

Article no:	AT1034
EAN:	8712259000145
Halogen free	Yes
Amount Packaging	36 st.
Conduit diameter	16 / 19 mm
Ø circular saw	80 mm
Outer size	105 mm
Mounting method	Concrete building
Degree of protection (IP)	IP20
Material	Plastic
Width	
Length	
Diameter	77 mm
Colour	Grey
Model	Single
Surface protection	Untreated
Circuit integrity	None
Cover model	None
Inner depth	100 mm
Degree of protection (NEMA)	-
Equipped with	-
Shape	Round
Pipe locking	No
Construction type	Central conduit box
Number of inlets	8
Air tight	No
For tube diameter	16/19 mm
Max. conductor cross section	6 mm ²
Inlet from the rear	No
Transparent cover	No
Cover attachment	Screwed
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	No
For number of electric fittings	
Mounting switching equipment	-
With screws	No
Housing feed-through by break-out opening	No
Housing feed-through by seal membrane	No

Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	-
Dispatch	36

The concrete ceiling junction boxes are specially developed for the installation of conventional systems in concrete ceilings. These junction boxes are equipped with combi-inlets combined for 16 mm and 19 mm conduits. The ceiling junction boxes Concrete are used in solid floors and concrete hollow-core floors, or precast slab floors.