


Kitvast concrete system junction boxes



CD100R Kitvast junction box with tape Ø 16/19 mm

- Applicable in wide slab floors and on tunnel formwork.
- Distance from the bottom of the conduit entry to the open side of the box: 80 mm.
- The penetration of concrete water into conduit entries is prevented by adhesive tape.
- Fitted with adhesive lid.
- Suitable covers for mounting: Art. no. AT5010 and AT5011.

Article no:	AT1039
EAN:	8712259280301
Halogen free	Yes
Amount Packaging	36 st.
Conduit diameter	16 / 19 mm
Ø circular saw	80 mm
Outer size	105 mm
Mounting method	Concrete building
Degree of protection (IP)	IP20
Material	Plastic
Width	
Length	
Diameter	77 mm
Colour	Grey
Model	Single
Surface protection	Untreated
Circuit integrity	None
Cover model	Construction protective cover
Inner depth	100 mm
Degree of protection (NEMA)	-
Equipped with	-
Shape	Round
Pipe locking	No
Construction type	Central conduit box
Number of inlets	8
Air tight	No
For tube diameter	16/19 mm
Max. conductor cross section	6 mm ²
Inlet from the rear	No
Transparent cover	No
Cover attachment	Snapped on
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	No
For number of electric fittings	
Mounting switching equipment	-
With screws	No
Housing feed-through by break-out opening	No
Housing feed-through by seal membrane	No

Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	-
Dispatch	36

Attema's Kitvast® concrete system is used in cement plants. After measurement, the box and cover are anchored in place with adhesive. After removal of the form, the cover and adhesive are removed from the form. The Kitvast® adhesive covers are designed in such a way that no adhesive residue is visible on the wall. Kitvast® is a flexible system that can be used on all surfaces without causing any damage to the form. Fixing by means of gluing (hot melt). Suitable for steel formwork. Fixing without drilling, i.e. no damage to formwork. Ideal for concrete plants.

- Attachment by means of gluing (hot melt).
- Suitable for steel formwork.
- Attachment without drilling, so no damage to formwork.
- Ideal for concrete factories.