

## Flush-mounted boxes Hollow-wall



### Conduit lead-in, double, 16/19 DUO-UHW50 Ø 16/19 mm

- Halogen-free.
- Applicable on DUO-UHW50.

|  |               |
|--|---------------|
| <b>Article no:</b>                     | <b>AT1059</b> |
| EAN:                                   | 8712259314686 |
| Amount Packaging                       | 50 st.        |
| Conduit diameter                       | 16 / 19 mm    |
| Suitable for built-in installation box | Yes           |
| Suitable for junction box              | No            |
| Suitable for cable box                 | No            |
| Suitable for expansion ring            | No            |
| For tube diameter                      | 16/19 mm      |
| Number of conduit lead-ins             | 2             |
| Dispatch                               | 50            |

Attema has a complete range of flush-mounted boxes for hollow walls. Such as fire and smoke resistant flush-mounted boxes, radiation resistant boxes and various inserts, making the boxes also suitable for applications where high(er) demands are made on the air and sound tightness of the walls. Part of the range are hollow wall flush-mounted boxes that are suitable for mounting with different kind of cables, so that they can be used in pluggable installations in utility and residential construction. A good example of this is the Installation 2.0 concept, in which the installation time is greatly reduced and the chance of errors is reduced to a minimum.