

## Flush-mounted boxes Hollow-wall



### DUO-UHW50 Hollow wall junction box Ø 16/19 mm

- Plate 1 - 43 mm.
- Plasterboard 9.5 - 43 mm.
- Equipped with separate combi spout.
- Equipped with 2 conical tube inlets with integrated locking for both 16 and 19 mm tube.
- Firm mounting of the box in the wall thanks to the metal screw plates with 3-fold pitch.
- No gap formation between switchgear and wall due to very thin, solid support edge of the metal fasteners.
- Distance to pipe inlet: 29 mm

<b>Article no:</b>	<b>AT1066</b>
EAN:	8712259312859
Amount Packaging	50 st.
Conduit diameter	16 / 19 mm
Ø circular saw	76 mm
Centre distance	71 mm
Inner size	50 mm
Mounting method	Hollow wall
Degree of protection (IP)	IP20
Material	Plastic
Width	76 mm
Length	144 mm
Diameter	76 mm
Halogen free	No
Colour	Grey
Model	Double
Surface protection	Untreated
Circuit integrity	None
Cover model	None
Inner depth	50 mm
Degree of protection (NEMA)	-
Equipped with	-
Shape	Round
Pipe locking	Yes
Construction type	Device connection box (round/square)
Number of inlets	2
Air tight	No
For tube diameter	16/19 mm
Max. conductor cross section	6 mm <sup>2</sup>
Inlet from the rear	No
Transparent cover	No
Cover attachment	-
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	Yes
For number of electric fittings	2
Mounting switching equipment	Screwing

With screws	Yes
Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	1
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	Double nozzle
With nail lugs	No
Special application	-
Dispatch	50

Attema has a complete range of flush-mounted boxes for hollow walls. Such as fire and smoke resistant flush-mounted boxes, radiation resistant boxes and various inserts, making the boxes also suitable for applications where high(er) demands are made on the air and sound tightness of the walls. Part of the range are hollow wall flush-mounted boxes that are suitable for mounting with different kind of cables, so that they can be used in pluggable installations in utility and residential construction. A good example of this is the Installation 2.0 concept, in which the installation time is greatly reduced and the chance of errors is reduced to a minimum.