

Flush-mounted boxes Hollow-wall



HWM600 Hollewand Montagestrip

- Metal mounting strip, applicable in the pre and pre-assembly of the cavity wall construction.
- A robust and stable fastener for the HWD50L.
- Applicable at 12.5 mm and 25 mm sheet thickness.
- When using the HWM600 and a HWD50L at 12.5 mm sheet thickness, the spacer (art. no. AT1058) provides additional stability in the installation construction.
- Possibility of 5 coupled hollow wall boxes at various positions in the hollow wall that can be installed simultaneously.
- To be placed from the front of the metallic uprights. This is independent of the total wall thickness.
- No impact noise when installing the installations in the hollow wall.
- Fixing width: 600 mm
- Hole diameter: 20 mm

Article no:	AT1083
EAN:	8712259326962
Amount Packaging	20 st.
Centre distance	71 mm
Type of accessory/spare part	-
Accessory	Yes
Spare part	No
Suitable for built-in installation box	Yes
Suitable for central conduit box	No
Dispatch	20

Attema has a complete range of flush-mounted boxes for hollow walls. Such as fire and smoke resistant flush-mounted boxes, radiation resistant boxes and various inserts, making the boxes also suitable for applications where high(er) demands are made on the air and sound tightness of the walls. Part of the range are hollow wall flush-mounted boxes that are suitable for mounting with different kind of cables, so that they can be used in pluggable installations in utility and residential construction. A good example of this is the Installation 2.0 concept, in which the installation time is greatly reduced and the chance of errors is reduced to a minimum.