


Fire-resistant hollow wall boxes



UHW50-BW / RD rookdichte Hollewand inbouwdoos Ø 16/19 mm

- Smokeproof :Sa and S200.
- Soundproofed.
- Maximum 90 minutes fire resistant in an insulated wall.
- Maximum 60 minutes fire resistant in a non-insulated wall.
- Tested in a non-load-bearing wall construction with 2 x 12,5 mm plasterboard panels on both sides.
- Halogen-free.
- Equipped with 2 conical tube inlets with integrated locking for both 16 and 19 mm tube.
- Firm mounting of the box in the wall thanks to the metal screw plates with 3-fold pitch.
- No gap formation between switchgear and wall due to very thin, solid support edge of the metal fasteners.
- Distance to pipe inlet: 29 mm

Article no:	AT1115
EAN:	8712259354583
Amount Packaging	25 st.
Conduit diameter	16 / 19 mm
Ø circular saw	76 mm
Centre distance	71 mm
Inner size	50 mm
Mounting method	Hollow wall
Degree of protection (IP)	IP20
Material	Plastic
Width	
Length	
Diameter	76 mm
Halogen free	Yes
Colour	Red
Model	Single
Surface protection	Untreated
Circuit integrity	E60
Cover model	None
Inner depth	44 mm
Degree of protection (NEMA)	-
Equipped with	-
Shape	Round
Pipe locking	Yes
Construction type	Device connection box (round/square)
Number of inlets	2
Air tight	Yes
For tube diameter	16/19 mm
Max. conductor cross section	6 mm ²
Inlet from the rear	No
Transparent cover	No
Cover attachment	-
Sealable	No
With screening	No
Provided with revolving ring	No

Connectable	Yes
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	Yes
Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	Double nozzle
With nail lugs	No
Special application	Fire protection
Dispatch	25

Attema has a complete range of hollow wall boxes for fire resistant hollow walls. These are just as easy to assemble as the standard hollow wall boxes. The fire resistant boxes are red, which makes them clearly distinguishable from hollow-wall boxes that are not provided with the fire resistant material. Depending on the type of wall and the application, a maximum fire resistance of 90 minutes is achieved.