

Flush-mounted boxes Hollow-wall



UHW50P-BW fire resistant Perilex hollow wall junction box for cable/cord 10 - 12 mm

- Halogen-free.
- Plate 1 - 35 mm.
- Plasterboard 9.5 - 27.5 mm.
- Equipped with 2 x Cable inlets Ø 10 - 12 mm.
- Firm mounting of the box in the wall thanks to the metal screw plates with 3-fold pitch.

Article no:	AT1124
EAN:	8712259338491
Amount Packaging	25 st.
Ø circular saw	76 mm
Inner size	50 mm
Mounting method	Hollow wall
Degree of protection (IP)	IP20
Material	Plastic
Width	
Length	
Diameter	76 mm
Halogen free	Yes
Colour	Red
Model	Perilex
Surface protection	Untreated
Circuit integrity	E60
Cover model	None
Inner depth	50 mm
Equipped with	None
Shape	Round
Suitable for cable diameter	10 - 12 mm
Pipe locking	No
Construction type	Built-in installation box (device box)
Number of inlets	2
Air tight	No
Max. conductor cross section	6 mm ²
Inlet from the rear	No
Transparent cover	No
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	No
For number of electric fittings	1
Suitable for wall/board thickness	1 - 35 mm
Mounting switching equipment	Screwing
With screws	Yes
Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No

Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	None
With nail lugs	No
Special application	Fire protection
Dispatch	25

Attema has a complete range of flush-mounted boxes for hollow walls. Such as fire and smoke resistant flush-mounted boxes, radiation resistant boxes and various inserts, making the boxes also suitable for applications where high(er) demands are made on the air and sound tightness of the walls. Part of the range are hollow wall flush-mounted boxes that are suitable for mounting with different kind of cables, so that they can be used in pluggable installations in utility and residential construction. A good example of this is the Installation 2.0 concept, in which the installation time is greatly reduced and the chance of errors is reduced to a minimum.