

## Flush-mounted boxes Traditional



### UK40 Compact junction box Ø 16 mm

- Mounting screws: M3 x 18 mm.
- Removable abdominal spout.
- For flush mounting of special double wall socket with earthed earthing.
- Internal dimensions: 65 x 100 mm
- Self-locking in hole 2 x 82 mm. heart-to-heart 35 mm.
- Halogen-free.

<b>Article no:</b>	<b>AT1139</b>
EAN:	8712259173467
Amount Packaging	50 st.
Conduit diameter	16 mm
Ø circular saw	2 x 82 mm
Inner size	40 mm
Mounting method	Flush mounted (plaster)
Degree of protection (IP)	IP20
Material	Plastic
Width	70 mm
Length	108 mm
Diameter	
Halogen free	Yes
Colour	Grey
Model	One and a half
Surface protection	Untreated
Circuit integrity	None
Cover model	Construction protective cover
Inner depth	40 mm
Degree of protection (NEMA)	-
Equipped with	-
Shape	Oval
Pipe locking	Yes
Construction type	Built-in installation box (device box)
Number of inlets	1
Air tight	No
For tube diameter	16 mm
Max. conductor cross section	6 mm <sup>2</sup>
Inlet from the rear	No
Transparent cover	Yes
Cover attachment	Snapped on
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	No
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	Yes
Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	No

Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	-
Dispatch	50

The complete line of flush-mounted boxes offers you the best, fastest installation in every situation. The traditional boxes are suitable for installation in materials such as calcium silicate brick, solid gypsum and cellular concrete. For every challenge there is a problem-solving flush-mounted box available from Attema. An advanced selection of parts completes the assortment.