

Flush-mounted boxes Traditional



NEW

UD50 Duo junction box

- Removable, flexible abdominal spout.
- Drill-hole Ø 82 mm.
- Suitable for conduit 16, 19 and 20 mm.
- Fastening screws M3 x 20 mm.
- Halogen-free.

Article no:	AT1144.01
EAN:	8712259577135
Amount Packaging	40 st.
Ø circular saw	82 mm
Inner size	50 mm
Mounting method	Flush mounted (plaster)
Degree of protection (IP)	IP20
Material	Plastic
Halogen free	Yes
Colour	Grey
Model	Double
Surface protection	Untreated
Circuit integrity	None
Inner depth	50 mm
Shape	Round
Pipe locking	No
Construction type	Built-in installation box (device box)
Number of inlets	4
Air tight	No
For tube diameter	16/19/20 mm
Max. conductor cross section	6 mm ²
Inlet from the rear	No
Transparent cover	Yes
Cover attachment	Snapped on
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	Yes
For number of electric fittings	2
Mounting switching equipment	Screwing
With screws	Yes
Housing feed-through by break-out opening	No
Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No

Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	None
Dispatch	40

The complete line of flush-mounted boxes offers you the best, fastest installation in every situation. The traditional boxes are suitable for installation in materials such as calcium silicate brick, solid gypsum and cellular concrete. For every challenge there is a problem-solving flush-mounted box available from Attema. An advanced selection of parts completes the assortment.