Flush-mounted boxes Hollow-wall



SHW50 Hollewand inbouwdoos loodvrij

- · Protection against X-rays up to a maximum lead equivalent of 3 mm Pb.
- Suitable for lead-free radiation protection walls (e.g. Knauf Safeboard).
- · Lead-free, harmless to health.
- · Can be installed in closed walls.
- · Rapid installation without additional protective measures.
- · Back to back mounting possible.
- · Halogen-free.

EAN: 8712259369082 Amount Packaging 10 st. Ø circular saw 74 mm Centre distance 71 mm Inner size 50 mm Mounting method Hollow wall Degree of protection (IP) IP20 Material Plastic Width Length Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection (NEMA) - Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Transparent cover No Cover attachment - Sealable Yes With screening Yes With screening Yes For number of electric fittings Mountings witching equipment With screens Ves For number of electric fittings Mountings witching equipment With screens With screens Ves With screens Ves For number of electric fittings Mounting switching equipment With screens Ves	Article no:	AT1147
Ø circular saw Centre distance Inner size Inner size So mm Mounting method Hollow wall Degree of protection (IP) Material Width Length Diameter Ta mm Halogen free Ves Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model Inner depth Degree of protection (NEMA) Equipped with Shape Round Suitable for cable diameter Pipe locking Yes Construction type Number of inlets 4 Air tight Yes Transparent cover Max. conductor cross section Inlet from the rear Yes Ves With screening Yes For rube diameter Yes For number of electric fittings No Connectable Yes For number of electric fittings Mounting switching equipment Screwing Mounting switching equipment Screwing No Corevalia	EAN:	8712259369082
Centre distance 71 mm Inner size 50 mm Mounting method Hollow wall Degree of protection (IP) IP20 Material Plastic Width Length Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes For number of electric fittings 1 Mounting switching equipment Mounting switching equipment Screwing	Amount Packaging	10 st.
Inner size 50 mm Mounting method Hollow wall Degree of protection (IP) IP20 Material Plastic Width Length Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes For number of electric fittings 1 Mounting switching equipment Screwing Mounting switching equipment Screwing Mounting switching equipment Screwing	Ø circular saw	74 mm
Mounting method Hollow wall Degree of protection (IP) IP20 Material Plastic Width Length Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Mounting switching equipment Screwing	Centre distance	71 mm
Degree of protection (IP) Material Material Plastic Width Length Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model Inner depth 50 mm Degree of protection (NEMA) Equipped with - Shape Round Suitable for cable diameter Pipe locking Construction type Number of inlets 4 Air tight Yes For tube diameter Transparent cover Max. conductor cross section Inlet from the rear Transparent cover Cover attachment Sealable Yes Provided with revolving ring No Connectable For number of electric fittings Mounting switching equipment Serewing 11 Mounting switching equipment Screwing Plastic Part mm Plastic Ves Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Inner size	50 mm
Material Plastic Width Length Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Mounting method	Hollow wall
Width Length Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Degree of protection (IP)	IP20
Length Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Material	Plastic
Diameter 74 mm Halogen free Yes Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Width	
Halogen free Yes Colour Yellow Model Single Surface protection Untreated Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Length	
ColourYellowModelSingleSurface protectionUntreatedCircuit integrityNoneCover modelNoneInner depth50 mmDegree of protection (NEMA)-Equipped with-ShapeRoundSuitable for cable diameter11.5 mmPipe lockingYesConstruction typeDevice connection box (round/square)Number of inlets4Air tightYesFor tube diameter-Max. conductor cross sectionInlet from the rearInlet from the rearYesTransparent coverNoCover attachment-SealableYesWith screeningYesProvided with revolving ringNoConnectableYesFor number of electric fittings1Mounting switching equipmentScrewing	Diameter	74 mm
ModelSingleSurface protectionUntreatedCircuit integrityNoneCover modelNoneInner depth50 mmDegree of protection (NEMA)-Equipped with-ShapeRoundSuitable for cable diameter11.5 mmPipe lockingYesConstruction typeDevice connection box (round/square)Number of inlets4Air tightYesFor tube diameter-Max. conductor cross section-Inlet from the rearYesTransparent coverNoCover attachment-SealableYesWith screeningYesProvided with revolving ringNoConnectableYesFor number of electric fittings1Mounting switching equipmentScrewing	Halogen free	Yes
Surface protection Untreated Circuit integrity None Cover model None Inner depth 50 mm Degree of protection (NEMA) - Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes For number of electric fittings 1 Mounting switching equipment Mone	Colour	Yellow
Circuit integrity Cover model Inner depth Degree of protection (NEMA) Equipped with - Shape Round Suitable for cable diameter Pipe locking Construction type Number of inlets Air tight For tube diameter Inlet from the rear Transparent cover Cover attachment Sealable With screening Provided with revolving ring No Connectable For number of electric fittings Mounting switching equipment No Cover attachment Screwing For number of electric fittings Mounting switching equipment Some	Model	Single
Cover modelNoneInner depth50 mmDegree of protection (NEMA)-Equipped with-ShapeRoundSuitable for cable diameter11.5 mmPipe lockingYesConstruction typeDevice connection box (round/square)Number of inlets4Air tightYesFor tube diameter-Max. conductor cross section-Inlet from the rearYesTransparent coverNoCover attachment-SealableYesWith screeningYesProvided with revolving ringNoConnectableYesFor number of electric fittings1Mounting switching equipmentScrewing	Surface protection	Untreated
Inner depth Degree of protection (NEMA) Equipped with - Shape Round Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Transparent cover No Cover attachment Sealable Yes With screening Provided with revolving ring Connectable For number of electric fittings Mounting switching equipment Sealable Screwing	Circuit integrity	None
Degree of protection (NEMA) Equipped with Shape Round Suitable for cable diameter Pipe locking Construction type Device connection box (round/square) Number of inlets Air tight Yes For tube diameter Max. conductor cross section Inlet from the rear Transparent cover Cover attachment Sealable Yes With screening Provided with revolving ring Connectable For number of electric fittings Mounting switching equipment - Round - Round - Round - No Trans No Tound/square) No For Sealable Yes No Cover attachment - Sealable Yes For number of electric fittings 1 Mounting switching equipment	Cover model	None
Equipped with Shape Round Suitable for cable diameter Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring Connectable For number of electric fittings Mounting switching equipment Sealable Screwing Round Seven Round Yes Provided Round Seven Round Seven Provided Round Seven Round Seve	Inner depth	50 mm
Shape Suitable for cable diameter 11.5 mm Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable For number of electric fittings Mounting switching equipment Sealable Screwing Provided Screwing	Degree of protection (NEMA)	-
Suitable for cable diameter Pipe locking Yes Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring Connectable For number of electric fittings Mounting switching equipment 11.5 mm 11.	Equipped with	-
Pipe locking Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter Max. conductor cross section Inlet from the rear Transparent cover No Cover attachment Sealable Yes With screening Provided with revolving ring Connectable For number of electric fittings Mounting switching equipment Pevice connection box (round/square) A 4 Ves Yes Yes No Connectable Yes For number of electric fittings 1 Mounting switching equipment	Shape	Round
Construction type Device connection box (round/square) Number of inlets 4 Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Suitable for cable diameter	11.5 mm
Number of inlets Air tight Yes For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring Connectable Yes For number of electric fittings Mounting switching equipment 4 Yes Yes No No Screwing	Pipe locking	Yes
Air tight For tube diameter - Max. conductor cross section Inlet from the rear Transparent cover No Cover attachment - Sealable Yes With screening Provided with revolving ring Connectable For number of electric fittings Mounting switching equipment Yes Yes Screwing	Construction type	Device connection box (round/square)
For tube diameter - Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Number of inlets	4
Max. conductor cross section Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Air tight	Yes
Inlet from the rear Yes Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	For tube diameter	-
Transparent cover No Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Max. conductor cross section	
Cover attachment - Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Inlet from the rear	Yes
Sealable Yes With screening Yes Provided with revolving ring No Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	Transparent cover	No
With screening Provided with revolving ring No Connectable For number of electric fittings Mounting switching equipment Yes 1 Screwing	Cover attachment	-
Provided with revolving ring Connectable For number of electric fittings Mounting switching equipment No Yes 1 Mounting switching equipment Screwing	Sealable	Yes
Connectable Yes For number of electric fittings 1 Mounting switching equipment Screwing	With screening	Yes
For number of electric fittings 1 Mounting switching equipment Screwing	Provided with revolving ring	No
Mounting switching equipment Screwing	Connectable	Yes
	For number of electric fittings	1
With screws Yes	Mounting switching equipment	Screwing
	With screws	Yes



Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	Yes
Housing feed-through by nozzle	Yes
Housing feed-through by step membrane	Yes
Pipe locking optional	Yes
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	Yes
Luminaire hook mounting	Yes
Nozzle	-
With nail lugs	Yes
Special application	-
Dispatch	10

Attema has a complete range of flush-mounted boxes for hollow walls. Such as fire and smoke resistant flush-mounted boxes, radiation resistant boxes and various inserts, making the boxes also suitable for applications where high(er) demands are made on the air and sound tightness of the walls. Part of the range are hollow wall flush-mounted boxes that are suitable for mounting with different kind of cables, so that they can be used in pluggable installations in utility and residential construction. A good example of this is the Installation 2.0 concept, in which the installation time is greatly reduced and the chance of errors is reduced to a minimum.

