

Flush-mounted boxes Hollow-wall



SHW50 Hollewand inbouwdoos loodhoudend

- Protection against X-rays up to a lead equivalent of max. 2.5 mm Pb.
- Suitable for lead-lined radiation protection walls.
- Harmless to health, no skin contact with lead component.
- Can be installed in closed walls.
- Rapid installation without additional protective measures.
- Back to back mounting possible.
- Halogen-free.

Article no:	AT1148
EAN:	8712259370651
Amount Packaging	10 st.
Ø circular saw	74 mm
Centre distance	71 mm
Inner size	50 mm
Mounting method	Hollow wall
Degree of protection (IP)	IP20
Material	Plastic
Width	
Length	
Diameter	74 mm
Halogen free	Yes
Colour	Grey
Model	Single
Surface protection	Untreated
Circuit integrity	None
Cover model	None
Inner depth	50 mm
Degree of protection (NEMA)	-
Equipped with	-
Shape	Round
Suitable for cable diameter	11.5 mm
Pipe locking	Yes
Construction type	Device connection box (round/square)
Number of inlets	4
Air tight	Yes
For tube diameter	-
Max. conductor cross section	
Inlet from the rear	Yes
Transparent cover	No
Cover attachment	-
Sealable	Yes
With screening	Yes
Provided with revolving ring	No
Connectable	Yes
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	Yes

Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	Yes
Housing feed-through by nozzle	Yes
Housing feed-through by step membrane	Yes
Pipe locking optional	Yes
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	Yes
Luminaire hook mounting	Yes
Nozzle	-
With nail lugs	Yes
Special application	-
Dispatch	10

Attema has a complete range of flush-mounted boxes for hollow walls. Such as fire and smoke resistant flush-mounted boxes, radiation resistant boxes and various inserts, making the boxes also suitable for applications where high(er) demands are made on the air and sound tightness of the walls. Part of the range are hollow wall flush-mounted boxes that are suitable for mounting with different kind of cables, so that they can be used in pluggable installations in utility and residential construction. A good example of this is the Installation 2.0 concept, in which the installation time is greatly reduced and the chance of errors is reduced to a minimum.