

## Flush-mounted boxes Traditional



### U50 Junction box Ø 16 mm, case 10 p.

- 360° degree rotating ring.
- Removable abdominal spout.
- Mounting screws: M3 x 18 mm.
- On the backside provided with break port for tube 16 mm.
- Extra pass-through option for linked boxes.
- Halogen-free.

<b>Article no:</b>	<b>AT1224</b>
EAN:	8712259256498
Amount Packaging	22 x 10 st.
Conduit diameter	16 mm
Ø circular saw	82 mm
Inner size	50 mm
Mounting method	Flush mounted (plaster)
Degree of protection (IP)	IP20
Material	Plastic
Width	
Length	
Diameter	82 mm
Halogen free	Yes
Colour	Grey
Model	Single
Surface protection	Untreated
Circuit integrity	None
Cover model	Construction protective cover
Inner depth	50 mm
Degree of protection (NEMA)	-
Equipped with	-
Shape	Round
Pipe locking	Yes
Construction type	Device connection box (round/square)
Number of inlets	1
Air tight	No
For tube diameter	16 mm
Max. conductor cross section	6 mm <sup>2</sup>
Inlet from the rear	Yes
Transparent cover	Yes
Cover attachment	Snapped on
Sealable	No
With screening	No
Provided with revolving ring	Yes
Connectable	Yes
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	Yes
Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	No

Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	-
Dispatch	22

The complete line of flush-mounted boxes offers you the best, fastest installation in every situation. The traditional boxes are suitable for installation in materials such as calcium silicate brick, solid gypsum and cellular concrete. For every challenge there is a problem-solving flush-mounted box available from Attema. An advanced selection of parts completes the assortment.