

New Record

**CHS75-ET4-BW, enkelpolige schakeling 2-voudig, brandwerend**

- 60 minutes fire-resistant
- Applicable in hollow ceiling constructions.
- Suitable for rachel ceilings and metal stud ceilings.
- Connectors from Wago-Winsta RD
- Equipped with 1x power supply (male black), 1x switch (female brown), 1x light point forwarding (female white), 1x light point on central box cover.

Article no:	AT1308
EAN:	8712259343433
Amount Packaging	1 st.
Ø circular saw	76 mm
Outer size	79 mm
Switched	1-pole 2-fold
Number of Outlets	4
Mounting method	Hollow ceiling
Degree of protection (IP)	IP20
Material	Plastic
Width	
Length	
Diameter	76 mm
Halogen free	Yes
Colour	Red
Model	Single
Surface protection	Untreated
Circuit integrity	E60
Cover model	Mounting cover
Inner depth	77 mm
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Round
Pipe locking	No
Construction type	Central conduit box
Number of inlets	12
Air tight	No
For tube diameter	16/19 mm
Max. conductor cross section	2.5 mm ²
Inlet from the rear	No
Transparent cover	No
Cover attachment	Screwed
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	No
For number of electric fittings	
Mounting switching equipment	-
With screws	No
Housing feed-through by break-out opening	No

Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	Yes
Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	Fire protection

Installeren RD is een stekerbaar installatiesysteem gebaseerd op voorbedrade centraaldozen of kabeldozen in combinatie met prefab gemonteerd schakelmateriaal en een stekerbare groepenkast. Deze onderdelen worden met soepele kabels met ronde connectoren aangesloten. De installatietijd wordt daardoor sterk bekort, en faalkosten worden tot een minimum beperkt. 100% Installeren is een samenwerkingsverband van Gira, Jung, PEHA, WAGO en Attema.