

Central junction boxes hollow ceiling



Plaster compensation ring, round junction boxes

- Stackable underneath.
- Universally applicable on any round central box.
- Application: thick(er) ceiling tiles (e.g. 2 x 12.5 mm plasterboard).
- Raising edge not provided with inserts and M4 screws not provided.

Article no:	AT1515
EAN:	8712259530703
Height	15 mm
Halogen free	Yes
Material	PP
Amount Packaging	50 st.
diameter	76 mm
Mounting method	Flush mounted (plaster)
Width	
Length	
Diameter	76 mm
Levelling height	15 mm
Shape	Round
With cover	No
Application	Central conduit box
Extension ring	Yes
Dispatch	50

The junction boxes for hollow ceilings can be used in any situation in the hollow ceiling structure. In rachel wood ceilings (eg. 18 mm and 22 mm) and metal Metal Stud ceilings (eg. 27 mm). Suitable for ceiling panel thicknesses of eg 9.5 mm, 12.5 mm and 25 mm. Applicable in standard and fire-resistant ceiling structures. The round shape of the junction boxes is easily applied in the ceiling plate when drilling the correct hole diameter (Ø 76 mm). The ceiling junction boxes are equipped with 12 combi-inlets. Suitable for 16 mm or 19 mm conduits and cable (via cable strain relief, Art. No. AT1062). The junction boxes can be performed pluggable with WINSTA RD connectors.