## **Splice junction boxes Traditional**




Article no:

**Amount Packaging** 

EAN:





3 3	
Conduit diameter	16 mm
Rated insulation voltage Ui	500 V
Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP40
Material	Plastic
Width	
Length	
Diameter	62 mm
Halogen free	Yes
Colour	White
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	32 mm
Cover model	None
Degree of protection (NEMA)	-
Equipped with	None
Shape	Round
Tackable	No
Number of inlets	3
For tube diameter	16 mm
Max. conductor cross section	6 mm <sup>2</sup>
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Pipe socket
Transparent cover	No
Cover attachment	Screwed
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	100

AT2061

10 x 10 st.

8712259002309

The complete assortment of round, splice junction boxes from Attema includes numerous combinations and positions of the conduit lead-ins. The Attema assortment includes solutions for every situation. Especially well suited for surface-mount installations for conduit and conduit clips.

