


## Splice junction boxes Universal



### Universal junction box, 16 mm, type LU

- Equipped with 8 breakout ports 16 mm.
- Tubes can be clicked in.
- Quick fastening possible by thumb-nail-clamping plug (art. no. AT9118).

<b>Article no:</b>	<b>AT2180</b>
EAN:	8712259002477
Halogen free	Yes
Amount Packaging	10 x 10 st.
Rated insulation voltage Ui	500 V
Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP40
Material	Plastic
Width	79 mm
Length	123 mm
Diameter	
Colour	White
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	42 mm
Cover model	None
Degree of protection (NEMA)	-
Equipped with	None
Shape	Rectangular
Tackable	No
Number of inlets	8
For tube diameter	16 mm
Max. conductor cross section	6 mm <sup>2</sup>
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	100

The universal splice junction boxes, types BK16/19 and type LU, with an extensive selection of components, each form a complete system. Both systems include covers with simplex and duplex outlets, with and without an integrated cover. The BK16/19 system also includes a large series of pre-assembled covers with adapters.