


Splice junction boxes Traditional

Top pull box Ø 16 mm, 2L,2R



Article no:	AT2211
EAN:	8712259002569
Amount Packaging	10 x 10 st.
Conduit diameter	16 mm
Rated insulation voltage Ui	500 V
Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP40
Material	Plastic
Width	
Length	
Diameter	62 mm
Halogen free	Yes
Colour	White
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	29 mm
Cover model	None
Degree of protection (NEMA)	-
Equipped with	None
Shape	Round
Tackable	No
Number of inlets	4
For tube diameter	16 mm
Max. conductor cross section	6 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Pipe socket
Transparent cover	No
Cover attachment	Screwed
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	100

The complete assortment of round, splice junction boxes from Attema includes numerous combinations and positions of the conduit lead-ins. The Attema assortment includes solutions for every situation. Especially well suited for surface-mount installations for conduit and conduit clips.