## Cable-mate® cableboxes for dry indoor use



## AK2-S/MD cable box for mesh cable trays

- · Packed per junction box 3 KBS 16 mm slide inlets and 1 shutter slide.
- Pre-assembled on plastic mounting plate MD for quick click-connection.
  Matching AK2 front part can be ordered separately.
- Universally applicable for all brands of wire tray.

EAN:8712259264004Halogen freeYesRated insulation voltage Ui690 VMounting methodOn cable trayDegree of protection (IP)IP40MaterialPlasticWidth95 mmLength120 mmDiameterUrtreatedColourGreySurface protectionNoneFor Ex-zone gasNoneFor Ex-zone gasNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMounting in the soilNoMounting in the soilNoMounting in the soilNoMounting in the soilNoShape of housing feed-throughPreembossingTransparent coverNoVict asting compoundNoSealableNoWith screeningNoWith screeningNoWith screeningNoVict asting compoundNoSealableNoWith screeningNoSealableNoWith screeningNoSealableNoWith screeningNoSealableNoWith screeningNoSealableNoWith screeningNo <th>Article no:</th> <th>AT2229</th>	Article no:	AT2229
Rated690 VMounting methodOn cable trayDegree of protection (IP)IP40MaterialPlasticWidth95 mmLength120 mmDiameterColourColourGreySurface protectionUntreatedExplosion-tested versionNoneFor Ex-zone gasNoneFor Ex-zone dustNoneOperating temperature-40 -70 °CCircuit integrityNoneDepth40 mmCover modelNoneShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMounting in the soilNoMounting in the soilNoMounting in the soilNoInlet from the rearNoNouring feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCover attachmentNoMounting in the soilNoWouting spleed-throughPreembossingTransparent coverNoVith casting compoundNoWith screeningNoWith	EAN:	8712259264004
Mounting methodOn cable trayDegree of protection (IP)IP40MaterialPlasticWidth95 mmLength120 mmDiameterColourColourGreySurface protectionUntreatedExplosion-tested versionNoFor Ex-zone gasNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting in the soilNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith screeningNoWith screeningNoWith screeningNoWith screeningNoWith screeningNoWith screeningNoWeatherproofNo	Halogen free	Yes
Degree of protection (IP)IP40MaterialPlasticWidth95 mmLength120 mmDiameterColourColourGreySurface protectionUntreatedExplosion-tested versionNoFor Ex-zone gasNoneOperating temperature-40 - 70 °CCircuit integrityNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tuing in the soilNoMounting in the soilNoMounting in the soilNoTarsparent coverNoCover attachmentSnaped onCort attachmentSnaped onMounting in the soilNoMounting compoundNoWith casting compoundNoWith casting compoundNoWith screeningNoWith screeningNoWith screeningNoWeatherproofNo	Rated insulation voltage Ui	690 V
MaterialPlasticWidth95 mmLength120 mmDiameterGreyColourGreySurface protectionUntreatedExplosion-tested versionNoFor Ex-zone gasNoneFor Ex-zone dustNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoWith casting compoundNoWith screeningNoWith screeningNoWith screeningNoWeatherproofNo	Mounting method	On cable tray
Width95 mmLength120 mmDiameterGreySurface protectionUntreatedExplosion-tested versionNoFor Ex-zone gasNoneFor Ex-zone dustNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoNouting under waterNoInlet from the rearNoTansparent coverNoCover attachmentSnapped onCover attachmentSnapped onGeratesting compoundNoWith casting compoundNoWith screeningNoWith screeningNoWith screeningNoWeatherproofNo	Degree of protection (IP)	IP40
Length120 mmDiameterColourGreySurface protectionUntreatedExplosion-tested versionNoFor Ex-zone gasNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter6 mm²Mounting in the soilNoMounting in the soilNoTarasparent coverNoCover attachmentSnapped onCover attachmentSnapped onWouting under waterNoMouting in the soilNoMouting compoundNoSupped onSnapped onCover attachmentSnapped onCover attachmentSnapped onCover attachmentSnapped onCover attachmentNoWith casting compoundNoWith screeningNoWith screeningNoWeatherproofNoWeatherproofNo	Material	Plastic
DiameterColourGreySurface protectionUntreatedExplosion-tested versionNoFor Ex-zone gasNoneFor Ex-zone dustNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter6 mm²Mounting under waterNoInlet from the rearNoTarasparent coverNoCover attachmentSnapped onVith casting compoundNoSupped from the rearNoSupped from the rearNoTarasparent coverNoWith casting compoundNoWith screeningNoWith screeningNoWith screeningNoWith screeningNoWeatherproofNoStapeNo	Width	95 mm
ColourGreySurface protectionUntreatedExplosion-tested versionNoFor Ex-zone gasNoneFor Ex-Zone dustNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMounting in the soilNoMounting under waterNoInlet from the rearNoTansparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoWith screeningNoWith screeningNoWeatherproofNo	Length	120 mm
Surface protectionUntreatedExplosion-tested versionNoFor Ex-zone gasNoneFor Ex-Zone dustNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoWith casting compoundNoWith casting compoundNoWith screeningNoWith screeningNoWeatherproofNo	Diameter	
Explosion-tested versionNoFor Ex-zone gasNoneFor Ex-Zone dustNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnaped onCastableNoWith casting compoundNoWith screeningNoWith screeningNoWeatherproofNo	Colour	Grey
For Ex-zone gasNoneFor Ex-Zone dustNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnaped onCastableNoWith casting compoundNoWith screeningNoWith screeningNoWeatherproofNoWeatherproofNo	Surface protection	Untreated
For Ex-Zone dustNoneOperating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoWith screeningNoWeatherproofNo	Explosion-tested version	No
Operating temperature-40 - 70 °CCircuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	For Ex-zone gas	None
Circuit integrityNoneDepth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoWith screeningNoWeatherproofNo	For Ex-Zone dust	None
Depth40 mmCover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoWith screeningNoWeatherproofNo	Operating temperature	-40 - 70 °C
Cover modelNoneDegree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoWith screeningNoWeatherproofNo	Circuit integrity	None
Degree of protection (NEMA)-Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoWith screeningNoWeatherproofNo	Depth	40 mm
Equipped withMounting plateShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoWith screeningNoWeatherproofNo	Cover model	None
ShapeRectangularTackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWeatherproofNo	Degree of protection (NEMA)	-
TackableNoNumber of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	Equipped with	Mounting plate
Number of inlets10For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWeatherproofNo	Shape	Rectangular
For tube diameter16 mmMax. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWeatherproofNo	Tackable	No
Max. conductor cross section6 mm²Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	Number of inlets	10
Mounting in the soilNoMounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	For tube diameter	16 mm
Mounting under waterNoInlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	Max. conductor cross section	6 mm²
Inlet from the rearNoType of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	Mounting in the soil	No
Type of housing feed-throughPreembossingTransparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	Mounting under water	No
Transparent coverNoCover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	Inlet from the rear	No
Cover attachmentSnapped onCastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	Type of housing feed-through	Preembossing
CastableNoWith casting compoundNoSealableNoWith screeningNoWeatherproofNo	Transparent cover	No
With casting compoundNoSealableNoWith screeningNoWeatherproofNo	Cover attachment	Snapped on
Sealable  No    With screening  No    Weatherproof  No	Castable	No
With screeningNoWeatherproofNo	With casting compound	No
Weatherproof No	Sealable	No
	With screening	No
Dispatch 100	Weatherproof	No
	Dispatch	100

## 

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.

