
## Cable-mate® cableboxes for dry indoor use





## AK2-S/VK IP40

- $\cdot\,$  Packed per junction box 3 KBS 16 mm slide inlets and 1 shutter slide.
- · Version with flat plastic mounting plate for quick click-mounting on cable trays.
- · Matching AK2 front part can be ordered separately.
- Suitable for cable trays from Legrand (Van Geel), Stago, Niedax, Vergokan, PUK and OBO.

Article no:	AT2250
EAN:	8712259161495
Halogen free	Yes
Rated insulation voltage Ui	690 V
Mounting method	On cable tray
Degree of protection (IP)	IP40
Material	Plastic
Width	95 mm
Length	120 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	40 mm
Cover model	None
Degree of protection (NEMA)	-
Equipped with	Mounting plate
Shape	Rectangular
Tackable	No
Number of inlets	10
For tube diameter	16 mm
Max. conductor cross section	6 mm²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	10

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.

