

Cable-mate® cableboxes for dry indoor use



AK2-SU enclosure base IP40

- For wall mounting (not suitable for attachment to wiring-duct mounting plate).
- Each cable box includes 3 slide-in KBS 16 mm and 1 slide-in blind cover.
- Matching AK2 front part can be ordered separately.

Article no:	AT2258
EAN:	8712259264745
Halogen free	Yes
Rated insulation voltage Ui	690 V
Mounting method	Universal
Degree of protection (IP)	IP40
Material	Plastic
Width	95 mm
Length	120 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	40 mm
Cover model	None
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Rectangular
Tackable	No
Number of inlets	10
For tube diameter	16 mm
Max. conductor cross section	6 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	15

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.