
## Cable-mate® cableboxes for watertight installation







## AK2-B IP65 Behuizing, zwart

- · Metric input M20.
- · Equipped with fixed seal.
- · Raised cover; easy to adapt for various industrial applications.
- · Bottom with mounting bosses for fastening DIN rails, among other things.
- · Each housing includes 2 closure plugs, 2 metal screws and a matching DIN rail type 35x7,5.

Each Housing medices 2 closure plags, 2 metal scients and a matering pint rain type 35%, 5.	
Article no:	AT2265.01
EAN:	8712259592398
Halogen free	Yes
Colour	Black
Protection rate	IP65
Rated insulation voltage Ui	690 V
Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP65
Material	Plastic
Width	95 mm
Length	120 mm
Diameter	
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	67 mm
Cover model	Blind cover
Equipped with	Support rail
Shape	Rectangular
Tackable	No
Number of inlets	8
Max. conductor cross section	6 mm²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Thread and prestamping
Transparent cover	No
Cover attachment	Snapped on
Castable	Yes
With casting compound	No
Sealable	No
With screening	No
Weatherproof	Yes
Dispatch	40

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.

