

Cable-mate® cableboxes for watertight installation



PA 20 cable gland

- Robust nylon cable gland with diaphragm seal M20, for applications in industrial environments and the agricultural sector.
- Clamping range Ø 7 - 13 mm, also suitable for residential wiring cable.
- Hex size: 23 mm.
- Tap length: 10 mm.

Article no:	AT2273
EAN:	8712259272146
Halogen free	Yes
Material	Plastic
Amount Packaging	50 st.
Protection rate	IP65
Degree of protection (IP)	IP68
Colour	Grey
RAL-number	7035
Model	Straight
Material quality	Polyamide (PA)
Surface protection	Untreated
With strain relief	Yes
Thread type	Metric
Nominal thread size metric/PG	20
Pitch thread	1.5 mm
Glass-fibre reinforced	No
Shock resistant	Yes
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-30 - 100 °C
Thread length	9 mm
EMC-version	No
Wrench width	24 mm
Suitable for cable diameter	7 - 13 mm
Hexagon angular dimension	26.3 mm
Bend radius protection/trumpet flare	No
With locknut	No
Snapping in opening	No
Multi seal area	No
Flat cable coupling	No
Type of sealing	Diaphragm
Separable screw gland	No
For armoured cable	No
Screened	No
Dispatch	50

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.