
## Cable-mate® cableboxes for watertight installation





- · Metric lead-in M20.
- · Equipped with fixed seal and closure plugs.
- · Symmetrical box.
- · Cover can be placed in any position.
- · Each cable box includes 3 nylon (PA) cable glands with diaphragm seal M20.
- M20 cable glands also suitable for residential wiring cable (clamping range: Ø 7 13 mm).



<u> </u>	
Article no:	AT2280
EAN:	8712259002644
Halogen free	Yes
Amount Packaging	20 x 5 st.
diameter	7-13 mm
Protection rate	IP65
Rated insulation voltage Ui	690 V
Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP65
Material	Plastic
Width	95 mm
Length	95 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	45 mm
Cover model	Blind cover
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Square
Tackable	No
Number of inlets	8
For tube diameter	-
Max. conductor cross section	6 mm <sup>2</sup>
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Thread and prestamping
Transparent cover	No
Cover attachment	Snapped on
Castable	Yes
With casting compound	No
Sealable	No
With screening	No
Weatherproof	Yes



Dispatch 100

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.

