

## Cable-mate® cableboxes for watertight installation



### AX4 IP55

- Includes 12 membrane lead-ins around the edge and 2 on the bottom.
- Lead-ins are suitable for cable Ø 2-14 mm
- Symmetrical box.
- Cover can be placed in any position.
- Dimensions: 85 x85 x37 mm (external).

<b>Article no:</b>	<b>AT2285</b>
EAN:	8712259256863
Halogen free	Yes
Amount Packaging	12 x 10 st.
Protection rate	IP55
Rated insulation voltage Ui	400 V
Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP55
Material	Plastic
Width	85 mm
Length	85 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	37 mm
Cover model	Blind cover
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Square
Tackable	No
Number of inlets	14
For tube diameter	-
Max. conductor cross section	2.5 mm <sup>2</sup>
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Seal membrane
Transparent cover	No
Cover attachment	Snapped on
Castable	Yes
With casting compound	No
Sealable	No
With screening	No
Weatherproof	Yes
Dispatch	120

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.