

## Cable-mate® cableboxes for dry indoor use

## AK2-IP40



- Metric input M20.
- Especially for mounting on steel mounting plates of cable trays.
- 3 cable/tube entries KBI 16 mm and 1 quick fastening screw are packed per cable box.

<b>Article no:</b>	<b>AT2291</b>
EAN:	8712259088600
Halogen free	Yes
Amount Packaging	20 x 5 st.
Protection rate	IP40
Rated insulation voltage Ui	690 V
Mounting method	Universal
Degree of protection (IP)	IP40
Material	Plastic
Width	95 mm
Length	120 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	45 mm
Cover model	Blind cover
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Rectangular
Tackable	No
Number of inlets	8
For tube diameter	16 mm
Max. conductor cross section	6 mm <sup>2</sup>
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Thread and prestamping
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	100

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.