


Cable-mate® cableboxes for watertight installation

Junction box AK2-IP65 M20 with base



- Metric input M20.
- For early mounting on cable tray mounting plates.
- Quick fastening screw included.
- Bottom with mounting bosses for fastening DIN rails, among other things.
- Matching AK2 front part can be ordered separately.

Article no:	AT2292
EAN:	8712259057477
Halogen free	Yes
Amount Packaging	5 x 10 st.
Rated insulation voltage Ui	690 V
Mounting method	Universal
Degree of protection (IP)	IP65
Material	Plastic
Width	95 mm
Length	120 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	45 mm
Cover model	None
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Rectangular
Tackable	No
Number of inlets	8
For tube diameter	16/19 mm
Max. conductor cross section	6 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Thread and prestamping
Transparent cover	No
Cover attachment	Snapped on
Castable	Yes
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	50

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.