


## Cable-mate® cableboxes for watertight installation



### Junction box type WD2

- Cover can be placed in any position.
- 3 nylon (PA) diaphragm cable glands M20 including lock nut without flange are packed per junction box (art. no. AT2522).
- Clamping range Ø 7 - 13 mm.

<b>Article no:</b>	<b>AT2300</b>
EAN:	8712259002682
Halogen free	Yes
Amount Packaging	20 x 5 st.
Protection rate	IP56
Rated insulation voltage Ui	500 V
Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP56
Material	Plastic
Width	88 mm
Length	88 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	45 mm
Cover model	Blind cover
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Square
Tackable	No
Number of inlets	7
For tube diameter	-
Max. conductor cross section	6 mm <sup>2</sup>
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	Yes
With casting compound	No
Sealable	No
With screening	No
Weatherproof	Yes
Dispatch	100

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.