

Cable-mate® cableboxes for watertight installation



NEW

PA 25 C Wartel met contraoer, zwart

- Robust nylon cable gland with M25 diaphragm seal, includes M25 lock-nut.
- Clamping range Ø10-17 mm.
- For use with junction box with combined M20/M25 knock-outs.
- Metric threads M25x1.5.
- Hex size: 29 mm.
- Tap length: 10 mm.

Article no:	AT2503.01
EAN:	8712259592831
Halogen free	Yes
Colour	Black
Material	Plastic
diameter	10-17 mm
Protection rate	IP68
Degree of protection (IP)	IP68
RAL-number	9005
Model	Straight
Material quality	Polyamide (PA)
Surface protection	Untreated
With strain relief	Yes
Thread type	Metric
Nominal thread size metric/PG	25
Pitch thread	1.5 mm
Glass-fibre reinforced	No
Shock resistant	Yes
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-30 - 100 °C
Thread length	10 mm
EMC-version	No
Wrench width	29 mm
Suitable for cable diameter	10 - 17 mm
Hexagon angular dimension	31.7 mm
Bend radius protection/trumpet flare	No
With locknut	Yes
Snapping in opening	No
Multi seal area	No
Flat cable coupling	No
Type of sealing	Diaphragm
Separable screw gland	No
For armoured cable	Yes
Screened	No
Dispatch	50

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.