

Empty boxes and parts

**PA 20 C cable gland with locking nut**

- Robust nylon cable gland with M20 diaphragm seal, includes M20 lock-nut.
- Clamping range Ø 7 - 13 mm.
- For use with junction box with combined M20/M25 knock-outs.
- Metric thread M20.
- Hex size: 23 mm.
- Tap length: 10 mm.

Article no:	AT2510
EAN:	8712259333298
Halogen free	Yes
Material	Plastic
Amount Packaging	50 st.
diameter	7-13 mm
Protection rate	IP68
Degree of protection (IP)	IP68
Colour	Grey
RAL-number	7035
Model	Straight
Material quality	Polyamide (PA)
Surface protection	Untreated
With strain relief	Yes
Thread type	Metric
Nominal thread size metric/PG	20
Pitch thread	1.5 mm
Glass-fibre reinforced	No
Shock resistant	Yes
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-30 - 100 °C
Thread length	9 mm
EMC-version	No
Wrench width	24 mm
Suitable for cable diameter	7 - 13 mm
Hexagon angular dimension	26.3 mm
Bend radius protection/trumpet flare	No
With locknut	Yes
Snapping in opening	No
Multi seal area	No
Flat cable coupling	No
Type of sealing	Diaphragm
Separable screw gland	No
For armoured cable	No
Screened	No
Dispatch	50

The new generation of Click-mate NXT distribution boxes is available in various versions: The compact S distribution box with 12 modules, the familiar M distribution box with space for 2 x 12 modules and the innovative L distribution cabinet with 2 x 18 modules; the solution for the energy transition and extensive 3-phase installations. The distribution boxes are also completely modular and can easily be installed next to or underneath each other.