

## Cable-mate® cableboxes for watertight installation

**NEW****PA 20 C Wartel met contraamoer, zwart**

- Robust nylon cable gland with M20 diaphragm seal, includes M20 lock-nut.
- Clamping range Ø 7 - 13 mm.
- For use with junction box with combined M20/M25 knock-outs.
- Metric thread M20.
- Hex size: 23 mm.
- Tap length: 10 mm.

<b>Article no:</b>	<b>AT2510.01</b>
EAN:	8712259592862
Halogen free	Yes
Colour	Black
Material	Plastic
diameter	7-13 mm
Protection rate	IP68
Degree of protection (IP)	IP68
RAL-number	9005
Model	Straight
Material quality	Polyamide (PA)
Surface protection	Untreated
With strain relief	Yes
Thread type	Metric
Nominal thread size metric/PG	20
Pitch thread	1.5 mm
Glass-fibre reinforced	No
Shock resistant	Yes
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-30 - 100 °C
Thread length	9 mm
EMC-version	No
Wrench width	24 mm
Suitable for cable diameter	7 - 13 mm
Hexagon angular dimension	26.3 mm
Bend radius protection/trumpet flare	No
With locknut	Yes
Snapping in opening	No
Multi seal area	No
Flat cable coupling	No
Type of sealing	Diaphragm
Separable screw gland	No
For armoured cable	No
Screened	No
Dispatch	50

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.