

Cable-mate® cableboxes for dry indoor use



Flat box

- Including mounting plate and cover.
- Dimensions: 120 x 120 x 40 mm.
- Break-out ports for M20 cable gland, GST 18/Winsta Midi 3-, 4- and 5-pole and BST14.
- Box can be adjusted in any direction.
- Quick installation on various central boxes and flush-mounted boxes.
- For possibilities of hole pattern, see the assembly instructions.
- Suitable for mounting in suspended ceilings and underfloor areas.
- This product is designed so that you can assemble it yourself.
- WAGO WINSTA® MIDI / Wieland gesis® CLASSIC GST18® 3-, 4- and 5-pole and BST14.

Article no:	AT2525
EAN:	8712259244600
Halogen free	Yes
Rated insulation voltage Ui	400 V
Mounting method	Universal
Degree of protection (IP)	IP40
Material	Plastic
Width	120 mm
Length	120 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	40 mm
Cover model	Blind cover
Degree of protection (NEMA)	-
Equipped with	None
Shape	Square
Tackable	No
Number of inlets	2
For tube diameter	-
Max. conductor cross section	4 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No

Dispatch

20

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.