

Flexible conduit



Conduit sleeve Ø 16 mm

- Provide an extremely solid connection without adhesive.
- Suitable for both rigid and flexible conduit.

Article no:	AT2807
EAN:	8712259003191
Amount Packaging	10 x 50 st.
Conduit diameter	16 mm
Material	Plastic
Halogen free	No
Colour	-
Model	Extraction proof
Material quality	-
Surface protection	Untreated
Quality of surface coating	-
Surface polished	No
Surface brushed	Yes
For nominal tube diameter	
Two piece	Yes
With inspection opening and cover	Yes
Separable	Yes
With lock function	Yes
Type of lock function	-
Material sealing	-
With outer thread	Yes
With inner thread	Yes
Eccentric	Yes
Dispatch	500

Attema has a wide range of flexible conduits for various applications.

Such as ZeroH-flex: halogen-free electroflex, where high(er) demands are made on fire-safe installations. Flame-retardant. KEMA approved according to NEN-EN-IEC 61386-1 and -22. Electroflex for standard electrical applications.

Attaflex, a halogen-free PE-conduit, resistant to higher temperatures and therefore especially suitable for use in concrete. Mantaflex: conduits suitable as thermal insulation material, for central heating or water pipes for instance. Can also be used as a protective hose for electrical connections of machines. And halogen-free Nylonflex, especially suitable for cables in situations where no toxic and corrosive gases may be released in the event of a fire.