

## Coupling-/repair closures

**Connecting sleeve, 6 fibres, CSP, 2 outlets**

- Compact dimensions: 120 x 95 x 55 mm (LxWxH)
- IP68 waterproof, according to EN 60529
- Klembereik wartel: Ø 5mm - Ø 10mm
- Securing the accompanying strain relief in the box
- Cassette is suitable for SM fiber optic G657A, R=23mm
- Suitable for 6x ANT and 6x Heatshrink Ø2.4 x 45mm welding protectors
- Individually packed in transparent foil, outer box of 5 pieces
- Assembly instructions included.
- Halogen-free

<b>Article no:</b>	<b>AT29016</b>
EAN:	8712259297781
Amount Packaging	5 st.
Degree of protection (IP)	IP68
Material	Plastic
Degree of protection (NEMA)	-
Lockable	No
Suitable for number of fibres	6
Type of coupler	Fusion splice
Separated compartments	No
Dispatch	5

Below-ground Fiber-to-the-Home networks are expanding at a steady rate. The European plans for the future are very ambitious. The more customer connection cables or ducts will be installed, the higher the risk that during the installation or afterwards failures due to excavation works will occur. In such event, it is of vital importance that the splice mechanic is able to repair the problem rapidly and in a compact manner. Next to repairing the closures can also be used for extending and/or connecting customer connection cables or ducts. This above-ground as well below-ground. Due to the universal character of the closures you will keep freedom of choice regarding the FttH concept. The clear sequence of actions enables the splice mechanic to execute his works rapidly and faultlessly using a compact closure. The IP68 waterproofness has been tested according to EN 60529.