

Coupling-/repair closures

**Repair sleeve CFD, cable, 5.0 - 6.5 mm, CSP, HS, IP68**

- Compact dimensions: Ø 85 mm x 155 mm
- IP68 waterproof, according to EN 60529
- Suitable for cable diameters Ø 5 mm - Ø 6.5 mm
- Integrated strain relief per cable
- Cassette is suitable for fiber optic with R = 22.5 mm
- The splice tray capacity is 2 splice connectors ANT/mini heatshrink or 2 splice protectors heatshrink Ø 2.4 mm x 45 mm.
- Packed individually in transparent foil

| | |
|-------------------------------|----------------|
| Article no: | AT29017 |
| EAN: | 8712259325132 |
| Colour | Black |
| Amount Packaging | 25 st. |
| diameter | 85 mm |
| Protection rate | IP68 |
| Degree of protection (IP) | IP68 |
| Material | Plastic |
| Degree of protection (NEMA) | - |
| Lockable | Yes |
| Suitable for number of fibres | 2 |
| Type of coupler | Fusion splice |
| Separated compartments | No |
| Dispatch | 25 |

Below-ground Fiber-to-the-Home networks are expanding at a steady rate. The European plans for the future are very ambitious. The more customer connection cables or ducts will be installed, the higher the risk that during the installation or afterwards failures due to excavation works will occur. In such event, it is of vital importance that the splice mechanic is able to repair the problem rapidly and in a compact manner. Next to repairing the closures can also be used for extending and/or connecting customer connection cables or ducts. This above-ground as well below-ground. Due to the universal character of the closures you will keep freedom of choice regarding the FttH concept. The clear sequence of actions enables the splice mechanic to execute his works rapidly and faultlessly using a compact closure. The IP68 waterproofness has been tested according to EN 60529.