Cable-mate® cableboxes for dry indoor use



Multi PD box, single, empty

- · Single MultiPD box.
- Dimensions box: 120 x 120 x 45 mm.
- $\cdot\,$ Stackable box with fixing lugs for screw and nail attachment.
- Outlet ports for M20 cable gland, GST18/Winsta Midi 3-, 4-, 5-pole and BST14.
- $\cdot\,$ This product is designed so that you can assemble it yourself.
- Box can be adjusted in any direction.
- · Suitable for spaces under raised floors and behind suspended ceilings.

Article no:	AT3001
EAN:	8712259309132
Halogen free	Yes
Rated insulation voltage Ui	400 V
Mounting method	Universal
Degree of protection (IP)	IP40
Material	Plastic
Width	120 mm
Length	120 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	45 mm
Cover model	Blind cover
Degree of protection (NEMA)	-
Equipped with	None
Shape	Square
Tackable	No
Number of inlets	9
For tube diameter	-
Max. conductor cross section	4 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	12



Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.

