

Cable-mate® cableboxes for dry indoor use

**MultiPD box, 1x5p black male + 1x5p black + 6x3p black L1/2/3
WIELAND**

- Complete pluggable MultiPD box.
- 1x 5-pin input and 2x 3-pin output L1, 2x 3-pin output L2, 2x 3-pin output L3 and 1x 5-pin output incl. locks.
- Coupling mounting plate with fixing ears, suitable for both screw and ejection mounting.
- Wiring: 2.5 mm²
- Dimensions double box: 240 x 120 x 45 mm

Article no:	AT3004
EAN:	8712259309446
Amount Packaging	1 st.
Specification	
Rated insulation voltage Ui	400 V
Mounting method	Universal
Degree of protection (IP)	IP20
Material	Plastic
Width	120 mm
Length	240 mm
Diameter	
Halogen free	Yes
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	45 mm
Cover model	Blind cover
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Rectangular
Tackable	No
Number of inlets	8
For tube diameter	-
Max. conductor cross section	4 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No

Dispatch

6

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.