

Cable-mate® cableboxes for dry indoor use

AK2-SU IP40 grey (RAL 7037)

- Each cable box includes 3 conduit lead-ins KBU 16/19 mm and 1 slide-in blind cover.
- Matching AK2 front part can be ordered separately.



Article no:	AT3950
EAN:	8712259334592
Halogen free	Yes
Amount Packaging	10 x 5 st.
Protection rate	IP40
Rated insulation voltage Ui	660 V
Mounting method	Universal
Degree of protection (IP)	IP40
Material	Plastic
Width	95 mm
Length	120 mm
Diameter	
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	40 mm
Cover model	Blind cover
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Rectangular
Tackable	No
Number of inlets	10
For tube diameter	16/19 mm
Max. conductor cross section	6 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No
Dispatch	50

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.