

Cable-mate® cableboxes for dry indoor use

**AK2-S/GZ/WIK 3p, double socket cover Wieland**

- 3-pole input and output, including locks.
- Equipped with quadruple wall socket.
- Pre-shaped plastic assembly bracket for quick click-assembly on all common cable ducts.
- Wiring: 2.5 mm²

| | |
|------------------------------|--------------------------|
| Article no: | AT4602 |
| EAN: | 8712259301075 |
| Specification | |
| Rated insulation voltage Ui | 400 V |
| Mounting method | On cable tray |
| Degree of protection (IP) | IP20 |
| Material | Plastic |
| Width | 95 mm |
| Length | 215 mm |
| Diameter | |
| Halogen free | Yes |
| Colour | Grey |
| Surface protection | Untreated |
| Explosion-tested version | No |
| For Ex-zone gas | None |
| For Ex-Zone dust | None |
| Operating temperature | -40 - 70 °C |
| Circuit integrity | None |
| Depth | 85 mm |
| Cover model | Cover with socket outlet |
| Degree of protection (NEMA) | - |
| Equipped with | Mounting plate |
| Shape | Rectangular |
| Tackable | No |
| Number of inlets | 6 |
| For tube diameter | - |
| Max. conductor cross section | 4 mm ² |
| Mounting in the soil | No |
| Mounting under water | No |
| Inlet from the rear | Yes |
| Type of housing feed-through | Preembossing |
| Transparent cover | No |
| Cover attachment | Snapped on |
| Castable | No |
| With casting compound | No |
| Sealable | No |
| With screening | No |
| Weatherproof | No |

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.