

Cable-mate® cableboxes for dry indoor use

**AK2-S/GZ/WIK 3p, cover 2x3p Wieland**

- 3-pole input and output, including locks.
- Cover with 2x3p chassis parts, including locks.
- Pre-shaped plastic assembly bracket for quick click-assembly on all common cable ducts.
- Wiring: 2.5 mm²
- Wiring: 2.5 mm²

Article no:	AT4621
EAN:	8712259302546
Specification	
Rated insulation voltage Ui	400 V
Mounting method	On cable tray
Degree of protection (IP)	IP20
Material	Plastic
Width	95 mm
Length	215 mm
Diameter	
Halogen free	Yes
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	70 mm
Cover model	Suitable for snap-in connector (manufacturer specific)
Degree of protection (NEMA)	-
Equipped with	Mounting plate
Shape	Rectangular
Tackable	No
Number of inlets	4
For tube diameter	-
Max. conductor cross section	4 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Preembossing
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.