

Kitvast concrete system junction boxes



KVD50 Kitvast Duo-box Ø 19 mm

- Fitted with adhesive lid.
- Equipped with conical tube inlet with tube snapper.
- Mounting screws: M3 x 18 mm.
- Dimensions of the box is according to 2 coupled MV50 boxes.

| | |
|---|--------------------------------------|
| Article no: | AT4843 |
| EAN: | 8712259280493 |
| Halogen free | Yes |
| Amount Packaging | 50 st. |
| Conduit diameter | 19 mm |
| Inner size | 50 mm |
| Mounting method | Concrete building |
| Degree of protection (IP) | IP20 |
| Material | Plastic |
| Width | 70 mm |
| Length | 144 mm |
| Diameter | 80 mm |
| Colour | Grey |
| Model | Double |
| Surface protection | Untreated |
| Circuit integrity | None |
| Cover model | Construction protective cover |
| Inner depth | 50 mm |
| Degree of protection (NEMA) | - |
| Equipped with | - |
| Shape | Round |
| Pipe locking | Yes |
| Construction type | Device connection box (round/square) |
| Number of inlets | 1 |
| Air tight | No |
| For tube diameter | 19 mm |
| Max. conductor cross section | 6 mm ² |
| Inlet from the rear | No |
| Transparent cover | No |
| Cover attachment | Snapped on |
| Sealable | No |
| With screening | No |
| Provided with revolving ring | No |
| Connectable | Yes |
| For number of electric fittings | 2 |
| Mounting switching equipment | Screwing |
| With screws | Yes |
| Housing feed-through by break-out opening | Yes |
| Housing feed-through by seal membrane | No |
| Housing feed-through by nozzle | No |
| Housing feed-through by step membrane | No |

| | |
|------------------------------|--------------------|
| Pipe locking optional | No |
| Number of included spouts | |
| Number of poles of the clamp | |
| Clamp position fixed | No |
| Luminaire hook mounting | No |
| Nozzle | Tunnel branch pipe |
| With nail lugs | No |
| Special application | - |
| Dispatch | 50 |

Attema's Kitvast® concrete system is used in cement plants. After measurement, the box and cover are anchored in place with adhesive. After removal of the form, the cover and adhesive are removed from the form. The Kitvast® adhesive covers are designed in such a way that no adhesive residue is visible on the wall. Kitvast® is a flexible system that can be used on all surfaces without causing any damage to the form. Fixing by means of gluing (hot melt). Suitable for steel formwork. Fixing without drilling, i.e. no damage to formwork. Ideal for concrete plants.

- Attachment by means of gluing (hot melt).
- Suitable for steel formwork.
- Attachment without drilling, so no damage to formwork.
- Ideal for concrete factories.