

## Magvast concrete system junction boxes



### MVD50 Magvast Duo-box Ø 19 mm

- Equipped with conical tube inlet with tube snapper.
- Mounting screws: M3 x 18 mm.
- Dimensions of the box is according to 2 coupled MV50 boxes.

<b>Article no:</b>	<b>AT4847</b>
EAN:	8712259280592
Halogen free	Yes
Amount Packaging	50 st.
Conduit diameter	19 mm
Inner size	50 mm
Mounting method	Concrete building
Degree of protection (IP)	IP20
Material	Plastic
Width	70 mm
Length	144 mm
Diameter	80 mm
Colour	Grey
Model	Double
Surface protection	Untreated
Circuit integrity	None
Cover model	None
Inner depth	50 mm
Degree of protection (NEMA)	-
Equipped with	-
Shape	Round
Pipe locking	Yes
Construction type	Device connection box (round/square)
Number of inlets	1
Air tight	No
For tube diameter	19 mm
Max. conductor cross section	6 mm <sup>2</sup>
Inlet from the rear	No
Transparent cover	No
Cover attachment	Snapped on
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	Yes
For number of electric fittings	2
Mounting switching equipment	Screwing
With screws	Yes
Housing feed-through by break-out opening	Yes
Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No

Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	No
Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	-
Dispatch	50

Attema's Magvast® concrete construction system is used mainly in concrete factories, but also on building sites. Magvast® works with magnets that are clamped into the boxes to prevent concrete water from entering the boxes.

After measuring, the magnets are placed on which the box is then placed. After the formwork is removed, the magnet remains behind on the steel table or formwork, after which it can be removed and reused. Magvast® is then ready for the next cycle. It is a flexible system that does not damage the formwork.

Attema has magnets for various types of boxes in its range. Magnets have a high clamping force (>100 kg).

Suitable for steel formwork.

Attached without drilling, so no damage to the formwork.