

Cable-mate® cableboxes for watertight installation

**AK2-B, IP65, 1x 3P male + 2x 3P**

- Equipped with insulated wire 2.5 mm².

Article no:	AT5460
EAN:	8712259268217
Amount Packaging	10 st.
Protection rate	IP65
Wiring	No
Rated insulation voltage Ui	400 V
Mounting method	Universal
Degree of protection (IP)	IP65
Material	Plastic
Width	95 mm
Length	120 mm
Diameter	
Halogen free	Yes
Colour	Grey
Surface protection	Untreated
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 70 °C
Circuit integrity	None
Depth	67 mm
Cover model	Suitable for snap-in connector (manufacturer specific)
Degree of protection (NEMA)	-
Equipped with	None
Shape	Rectangular
Tackable	No
Number of inlets	8
For tube diameter	-
Max. conductor cross section	6 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	Yes
Type of housing feed-through	Thread and prestamping
Transparent cover	No
Cover attachment	Snapped on
Castable	Yes
With casting compound	No
Sealable	No
With screening	No
Weatherproof	Yes
Dispatch	10

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The patented raceway click attachment system makes rapid installation possible on all common raceways.