Attachments



Flat corner F25FW cream (RAL 1013)

- $\cdot\,$ With special guide piece to bend entire conduit content around corner, with minimal radius of 25 mm.
- Temporary mounting using click attachment to Z25 / F25 conduit. Definitive mounting by means of retaining collars under cover.
- · Overlaps the cover 5 mm. It is unnecessary to cut perfectly square at exactly the right length.

| Article no: | AT5604 |
|--------------------------------|---------------------|
| EAN: | 8712259273570 |
| Colour | - |
| Amount Packaging | 5 x 10 st. |
| Degree of protection (IP) | - |
| Material | Plastic |
| Height | 13 mm |
| Width | 25 mm |
| Halogen free | Yes |
| Type of fastening | Snap on |
| RAL-number | 1013 |
| Model | Base unit and cover |
| Material quality | Other |
| Surface protection | Untreated |
| Anti-bacterial treatment | No |
| Impact strength | - |
| Suitable for circuit integrity | Yes |
| With protective foil | No |
| Angle | 90 - 90 ° |
| Dispatch | 50 |

Z25 and F25 are the surface-mounted systems for installation-friendly data cabling. Thanks to the smart accessories, the entire contents of the tubes can be used for data cables up to Ø 10 mm. The handy connectors, branch pieces and end pieces ensure a neat finish.

