

Installeren 2.0 Snoeren



Eca - aansluitsnoer schakelaar, 12 meter

- Toepasbaar in holle ruimtes
- Onderhoudsvrij volgens EN-IEC 61535
- Voorzien van Attema connectoren

Article no:	AT8321.12
EAN:	8712259589206
Amount Packaging	5 st.
Fire class	Eca
Line function	brickAttribute.lineFunction.line-func-0
Cable type	H05VV-F
Length (M)	12 mmm
Number of poles	3
Rated voltage	400 V
Rated current	16 A
Degree of protection (IP)	IP20
Pollution degree	2
Halogen free	No
Colour outer sheath	Brown
Reaction-to-fire according to EN 13501-6: Class	Eca
Total length	12000 mm
Rated surge voltage	4 kV
Cable diameter	7.9 - 7.9 mm
Mechanical coding	Yes
Housing colour	Black
Pole codification	1, 2, 3
Colour coding/contact insert	Brown
Locking mechanism	Integrated in plug-in connector
Fire load	3.24 kWh
Surface treatment contacts	Tinned
Continuity resistance	
Type of finished cable	Other
Type side 1	Plug
Type side 2	Free conductor end
Conductor end treatment	Ultrasonic compressed wire ends
Dismantle length	90 mm
Strip length	12 mm
Nominal cross section conductor	1.5 mm ²
Insulating piece permanent temperature-resistant	90 °C
Cable permanent temperature-resistant to	60 °C
Max. operating temperature at conductor	50 °C
Dispatch	5

Installeren 2.0 is een stekbaar installatiesysteem gebaseerd op voorbedrade centraal- en kabeldozen in combinatie met prefab gemonteerd schakelmateriaal en een stekerbare groepenkast. Deze onderdelen worden met soepele kabels aangesloten. De installatietijd wordt daardoor sterk bekort ten opzichte van traditioneel installeren, en faalkosten worden tot een minimum beperkt.