

## Stekerbare centraaldozen

**CW75-E3, enkelpolige schakeling**

- Applicable in hollow ceiling constructions.
- Suitable for rachel ceilings and metal stud ceilings.
- Attema connectoren Installeren 2.0

|                                           |                     |
|-------------------------------------------|---------------------|
| <b>Article no:</b>                        | <b>AT8400-3</b>     |
| EAN:                                      | 8712259551777       |
| Amount Packaging                          | 1 st.               |
| Ø circular saw                            | 76 mm               |
| Outer size                                | 79 mm               |
| Fireproof                                 | No                  |
| Switched                                  | 1-pole              |
| Number of Outlets                         | 3                   |
| Mounting method                           | Hollow ceiling      |
| Degree of protection (IP)                 | -                   |
| Material                                  | Plastic             |
| Width                                     |                     |
| Length                                    |                     |
| Diameter                                  | 76 mm               |
| Halogen free                              | Yes                 |
| Colour                                    | Grey                |
| Model                                     | Single              |
| Surface protection                        | -                   |
| Circuit integrity                         | None                |
| Cover model                               | Mounting cover      |
| Inner depth                               | 77 mm               |
| Degree of protection (NEMA)               | -                   |
| Equipped with                             | Other               |
| Shape                                     | Round               |
| Depth                                     | 79 - 79 mm          |
| Pipe locking                              | Yes                 |
| Construction type                         | Central conduit box |
| Number of inlets                          | 12                  |
| Air tight                                 | Yes                 |
| For tube diameter                         | 16/19 mm            |
| Max. conductor cross section              | 2.5 mm <sup>2</sup> |
| Inlet from the rear                       | No                  |
| Transparent cover                         | No                  |
| Cover attachment                          | Screwed             |
| Sealable                                  | No                  |
| With screening                            | No                  |
| Provided with revolving ring              | No                  |
| Connectable                               | No                  |
| For number of electric fittings           |                     |
| Mounting switching equipment              | -                   |
| With screws                               | No                  |
| Housing feed-through by break-out opening | No                  |

|                                       |                    |
|---------------------------------------|--------------------|
| Housing feed-through by seal membrane | No                 |
| Housing feed-through by nozzle        | No                 |
| Housing feed-through by step membrane | No                 |
| Pipe locking optional                 | No                 |
| Number of included spouts             |                    |
| Number of poles of the clamp          |                    |
| Clamp position fixed                  | No                 |
| Luminaire hook mounting               | Yes                |
| Nozzle                                | Tunnel branch pipe |
| With nail lugs                        | No                 |
| Special application                   | Other              |

Installeren 2.0 is een stekerbaar installatiesysteem gebaseerd op voorbedrade centraal- en kabeldozen in combinatie met prefab gemonteerd schakelmateriaal en een stekerbare groepenkast. Deze onderdelen worden met soepele kabels aangesloten. De installatietijd wordt daardoor sterk ingekort ten opzichte van traditioneel installeren en faalkosten worden tot een minimum beperkt.